

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>A61M</b>	<b>A2</b>	<b>(11) International Publication Number:</b> <b>WO 96/39206</b> <b>(43) International Publication Date:</b> 12 December 1996 (12.12.96)
<b>(21) International Application Number:</b> PCT/IL96/00004 <b>(22) International Filing Date:</b> 5 June 1996 (05.06.96) <b>(30) Priority Data:</b> 114022 6 June 1995 (06.06.95) IL <b>(71) Applicant (for all designated States except US):</b> ASN RESPIRATION DEVICE LTD. [IL/IL]; Technology Center, 20179 Misgav (IL). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> OREN, Nathan [IL/IL]; 56 Morad Hagay, 21752 Carmiel (IL). <b>(74) Agent:</b> COHEN ZEDEK & RAPAPORT; 29 Bezael Street, 64683 Tel-Aviv (IL).		<b>(81) Designated States:</b> AT, AU, BG, BR, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, HU, IS, JP, KR, LT, LU, LV, MX, NO, NZ, PL, PT, RO, RU, SE, SG, SI, SK, TR, UA, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>
<b>(54) Title:</b> RESPIRATION DEVICE  <b>(57) Abstract</b>  A respiration mask to prevent sleep apnea and snoring comprising means for measuring the real time pressure inside the mask, and means for maintaining a predetermined pressure inside the mask. The mask is self-contained and does not require external air compression means.		

BEST AVAILABLE COPY

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## RESPIRATION DEVICE

The present invention relates to respiration aids, particularly for use by patients suffering from the disease known as Sleep Apnea and snoring. Sleep Apnea, which manifests itself by intensive snoring during sleep, is a biological disorder of the respiratory channels, in particular the upper air passages which tend to collapse and become blocked towards the end of some exhalation cycles. In order to overcome and avoid suffocation, the patient must exert an effort to continue the breathing process, i.e. the inhalation phase, which effort entails his actual awaking. Patients are thus driven in to a serious mental and physical condition, due to accumulated lack of sleep; although the patients seem to be asleep, actually they are not deriving the benefits of slumber, not to mention the inconvenience caused by people in proximity.

In the course of research, it has been found that great relief is attained if, by some external means, the patient's lungs (and, of course, the upper bronchial passages included) are kept under a constant, slightly elevated air pressure, of the order of 5-15 cm H<sub>2</sub>O above the ambient, "atmospheric" pressure.

Apparatus devised for the application of this kind of treatment included a belted nose-mask and snorkel, through which excessive quantity of air was supplied to the patient (of the order of 100 lit/min while normal human air consumption during sleep is about 6 lit/min).

This method assured that both the inhalation and the exhalation took place under practically the same, elevated pressure, as required. However, it has been found that the supply to the patient's mask of such extremely high quantities of air causes great inconvenience, expressed, inter alia, by extensive cooling and/or drying up of the nose and other breathing passages.

It has already been proposed to overcome this inherent deficiency of the conventional system - cf. Israel Patent Application No. 82300; however the apparatus therein disclosed still requires the installation of an electric motor to drive an indispensable compressor.

It is, therefore, the prime object of the present invention to provide a respiration device for the above purpose which is self-contained, and does not require an electrically powered air compressor.

The device of the invention is a respiration aid device, particularly for preventing snoring and Sleep Apnea, comprising a nose cover, a one-way inhalation, air valve, an exhalation controlled air, valve, a potentiometer for setting of in-mask pressure, a pressure gauge, two analog-to-digital (A/D) units, comparator, a controller.

The invention is illustrated in Fig. 1. Nothing in the following description is meant to limit the scope of the invention; it is meant only to clarify and illustrate it.

The device of the invention comprises a mask covering the patient's nose, and a servo mechanism maintaining inside the mask a desired pressure during exhalation. This pressure inside the mask is due to the patient's exhalation only.

As illustrated the novel device comprises a mask 1 to be attached to the face by means of a strap around the head. There are provided two valves, and inflow valve (2) and an outflow valve 3, which, allow air to flow from the outside into the mask and from the mask to the outside, respectively. The opening and closing of the one-way inflow valve is controlled by that valve's mechanism; the opening and closing of the outflow valve are controlled by control means 8.

3

There is provided a pressure gauge (5) which senses the air pressure inside the mask. A potentiometer (4) is set so that its resistance is used as reference. This reference corresponds to the desired threshold value of air pressure. Units marked on a scale, for setting the potentiometer, are units of pressure, given in mm of water above atmospheric pressure, in the range of 0 to 150 mm. There is provided two A/D converters (6 and 6') one for the air-pressure information coming from the pressure gauge and the other receiving reference information coming from potentiometer (4), convert these two analog data into digital data: the analog pressure information into digital pressure-information, and the analog resistance information into digital reference-information. These are input to a comparator which compares them with each other. According to this comparison the comparator 7 sends information to the controller 8. If the pressure measured by the pressure gauge is higher than the set reference, the comparator 7 sends to the controller 8 information to open the outflow valve 6'. If the pressure measured by the pressure gauge is lower than the set reference, the comparator sends to the controller 8 information to keep the outflow valve 6' closed.

Both valves are very sensitive and respond rapidly to very small pressure differences.

Various outflow valve, can be used, such as:

- (1) and on/off valve;
- (2) a valve with variable opening: from fully closed to fully open.

During inhalation the pressure within the mask 1 is lower than the pressure corresponding to the set reference so that the outflow valve 3 is closed and the patient inhales through the inflow valve 2. During exhalation the pressure within the mask 1 builds up because the two valves are closed. When the pressure within the mask exceeds the pressure corresponding to the set reference the control 8 sends information to the outflow valve 3 to open it, allowing air to flow out.

4

If the outflow valve 3 is of the on/off type it remains open until the pressure within the mask 1 reaches the pressure corresponding to the set reference and the outflow valve closes. If the outflow valve 3 is of the variable-opening type it opens in proportion to the pressure within the mask so that the pressure remains at the level corresponding to the set reference, and when it drops below that threshold, the valve closes.

It will thus be readily appreciated that the device provided according to the invention, is of simple construction; needs not be associated with auxiliary installations such as an electrical power source; it comprises a small number of simple elements and is therefore not liable to wear during prolonged use, and also inexpensive.

**CLAIMS**

1. A respiration mask, particularly for preventing sleep Apnea and snoring, comprising:  
a nose cover, provided with an inhalation, one-way, air valve; and  
exhalation, controlled, air valve; a potentiometer for reset timing in-mask pressure; a pressure gauge; two analog-to-digital circuits; a comparator and controller means, thus providing means for controlling the exhalation valve to maintain in-mask pressure during exhalation at a preset value.
2. A mask according to claim 1, where the opening and closing of the one-way outflow valve is controlled by control means.
3. A mask according to claim 1 or 2, where means are provided for establishing in the mask a pressure in the range of from about 0 to 150 mm water.
4. A mask where a pressure gauge senses air pressure inside the mask and a potentiometer set so that its resistance serves as reference, according to which preset difference the air pressure in the mask is maintained.
5. A system according to any of claims 1 to 4, where there are provided A/D converters, one for sensing air pressure from the pressure gauge, the other from the potentiometer, which data are used as input to a comparator which sends commands to the outflow valve, either opening it or leaving it in the closed state.
6. A respiration aid device for preventing Sleep Apnea and snoring substantially as hereinbefore described with reference to the accompanying drawing.

1/1




FIG. 1



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**